





H3

1200 x 1000 mm





Art. no. 83180801

Technical data *1			
Dimensions Lx Wx H (mm)	1200 x 1000 x 160		
Weight (kg)	22.0		
Material*2	HDPE, Virgin material		
Load capacity (kg)*3	Static 5000	Dynamic 1250	In racking system 850

Characteristics

Colour: light grey Runners: 3, welded Rims: 7 mm

Temperature stability: -30 °C to +40 °C, briefly up to +90 °C

Options

Central box retainers
Palgrip®anti-slip runners

Loading quantities (pcs/approx.)

Container Contain Contain

Container 20': 141 Container 40' High Cube: 340 Conventional trailer 45' high cube container: 390


Truck

MEGA-Trailer: 468

Jumbo: 504-540

Labelling options

Customised printing and numbering available on request depending on quantity. Position upon consultation.









- *1All technical data include characteristic features, which have been tested under specially defined conditions. Varying data may result from different conditions of usage such as loading method, prevailing temperature and length of storage time. All data and specified information are subject to change without notice. Our service team is pleased to be at your disposal to check the special requirements of your individual application.
- ^{*2} Our service team is pleased to be at your disposal if you require exact information about material compositions.
- *3 Static load: resistance to pressure on a flat ground surface and an evenly distributed load at a room temperature of approx. 20°C.
 Dynamic load: on a forklift with an evenly distributed load at a room temperature of approx. 20°C.
 In racking system: evenly distributed load (sacks) along the longitudinal sides. Resting on two supports for over 100h at a room temperature of approx. 20°C.

e-mail: jf@logeq.eu

www.logeq.eu