BAC 130





Features	BAC 130
Outer dimensions in mm	800 W x 600 D x 715 H
Inner dimensions in mm	620 W x 410 D x 520 H
Volume	138 liters
K Value	0,40 W/m².K
Weight	31 Kg
Insulation material	Expended polyurethane foam
Material of the walls	Rotomoulded polyethylene

Specifications and optional equipment



Standard equipment

B Eutectic plate support

Optional equipment

- A Eutectic plate TOP 130
- N Castor base fitted with 2 fixed and 2 swivelling wheels ø 100 mm
- O Castor base fitted with 2 fixed and 2 swivelling wheels ø 100 mm with brake
- P Castor base fitted with 4 swivelling wheels ø 100 mm, 2 with brake.

Tel : + 33 (0)4 77 906 863 Fax : + 33 (0)4 77 903 495 www.olivo.fr



Technical features

1

- Body and lid made of one piece rotomoulded polyethylene. Insulation with CFC free expanded polyurethane foam.
- 5 Monobloc silicon seal
- 6 Label holder
- 10 Hinging from moulding and 115° lid opening. °
- 11 Flush mounted and recessed fastener
- **13** Stackable BAC 130 with embossed bottom and lid from moulding.
- 15 8 Integrally moulded handles