




**CS3**  
1200 x 1000 mm



Art. no. 83229811

#### Technical data <sup>\*1</sup>

Dimensions L x W x H (mm)	1200 x 1000 x 150		
Weight (kg)	18.0		
Material <sup>*2</sup>	HDPE, Regranulated material		
Load capacity (kg) <sup>*3</sup>	 Static 5000	 Dynamic 1000	 In racking system 800



#### Characteristics

Colour: basalt grey  
Runners: 3,  
welded Rims: 7  
mm  
Temperature stability: -30 °C to +40 °C, briefly up to +90 °C

#### Options


Transponder  
Reinforcement profiles  
Rim options  
Palgrip® anti-slip runners

#### Loading quantities (pcs/approx.)

 Container	Container 20': 140 Container 40': 330	Container 40' High Cube: 365 Conventional trailer 45' high cube container: 416
 Truck	MEGA-Trailer: 494	Jumbo: 532-570

#### Labelling options

Customised printing and numbering available on request depending on quantity. Position upon consultation.



<sup>\*1</sup> All technical data include characteristic features, which have been tested under specially defined conditions. Varying data may result from different conditions of usage such as loading method, prevailing temperature and length of storage time. All data and specified information are subject to change without notice. Our service team is pleased to be at your disposal to check the special requirements of your individual application.

<sup>\*2</sup> Our service team is pleased to be at your disposal if you require exact information about material compositions.

<sup>\*3</sup> Static load: resistance to pressure on a flat ground surface and an evenly distributed load at a room temperature of approx. 20 °C.  
Dynamic load: on a forklift with an evenly distributed load at a room temperature of approx. 20 °C. In racking system: evenly distributed load (sacks) along the longitudinal sides. Resting on two supports for over 100 h at a room temperature of approx. 20 °C.