




D11200x800mm



Technical data *1			
Dimensions LxWxH(mm)	1200 x 800 x 150		
Weight (kg)	120		
Material*2	HDPE, Virgin material		
Load capacity (kg)*3	Static 5000	Dynamic 1000	In racking system 400

Characteristics Options

Colour: redbrown Transponder
Runners: 3, unwelded Reinforcement profiles

Temperature stability: -30 °C to +40 °C, briefly up to +90 °C Rim options

Antislip


Loading quantities (pcs/approx.)

Container Container 20': 215 Container 40' High Cube: 490 Conventional trailer 45' high cube container: 544

Truck MEGA-Trailer: 646 Jumbo: 684-722

Labelling options

Customised printing and numbering available on request depending on quantity. Position upon consultation.









- *1 All technical data include characteristic features, which have been tested under specially defined conditions. Varying data may result from different conditions of usage such as loading method, prevailing temperature and length of storage time. All data and specified information are subject to change without notice. Our service team is pleased to be at your disposal to check the special requirements of your individual application.
- *2 Our service team is pleased to be at your disposal if you require exact information about material compositions.
- *3 Static load: resistance to pressure on a flat ground surface and an evenly distributed load at a room temperature of approx. 20°C. Dynamic load: on a forklift with an evenly distributed load at a room temperature of approx. 20°C. In racking system: evenly distributed load (sacks) along the longitudinal sides. Resting on two supports for over 100h at a room temperature of approx. 20°C.

e-mail: jf@logeq.eu;

Phone: +371 29556922, +371 27025030;