






D3 ECO

1200x1000mm



Art. no. 83325200

Technical data *1

Dimensions L x W x H (mm)	1200 x 1000 x 150
Weight (kg)	140
Material*2	HDPE, Regranulated material
Load capacity (kg)*3	<div>  Static 5000 </div> <div>  Dynamic 1000 </div> <div>  In racking system 400 </div>



Characteristics

Colour: black
 Runners: 3, unwelded
 Temperature stability: -30 °C to +40 °C, briefly up to +90 °C
 Manufactured from regnanulated material of one single type

Options



Transponder
 Reinforcement profiles
 Rim options
 Antislip

Loading quantities (pcs/approx.)

 Container	Container 20': 140	Container 40' High Cube: 365
	Container 40': 330	Conventional trailer 45' high cube container: 416
 Truck	MEGA-Trailer: 494	Jumbo: 532-570

Labelling options

Customised printing and numbering available on request depending on quantity. Position upon consultation.



*1 All technical data include characteristic features, which have been tested under specially defined conditions. Varying data may result from different conditions of usage such as loading method, prevailing temperature and length of storage time. All data and specified information are subject to change without notice. Our service team is pleased to be at your disposal to check the special requirements of your individual application.

*2 Our service team is pleased to be at your disposal if you require exact information about material compositions.

*3 Static load: resistance to pressure on a flat ground surface and an evenly distributed load at a room temperature of approx. 20 °C.

Dynamic load: on a forklift with an evenly distributed load at a room temperature of approx. 20 °C.

In racking system: evenly distributed load (sacks) along the longitudinal sides. Resting on two supports for over 100 h at a room temperature of approx. 20 °C.