

# **ROLL 650**



## Specifications and optional equipment

Features	ROLL 650
Outer dimensions in mm	740 W x 940 D x 1840 H
Inner dimensions in mm	565 W x 760 D x 1500 H
Volume	644 litres
K value	0,38 W/m².K
Weight	100 Kg
Insulation material	Expanded polyurethane foam
Material of the walls	Rotomoulded polyethylene

	4
5 CONDELIVIAISON 15 16 16 16 16 16 16 16 16 16 16	
	G

#### Standard equipment

B Eutectic plate support

### **Optional equipment**

- A Eutectic plate TOP 900
- C Dry ice drawer
- F 2 brake wheels ø 100 mm
- G 4 metal feet ø 60 mm
- H 3 removable shelves plastic coated
- I 3 removable shelves stainless steel

#### **Technical features**

- Body and door made of one piece rotomoulded polyethylene. Grooves on internal walls facilitate cold gas flow natural convection
- 2 Body/door hinging with 2 pins
- 2-points « Pélican » closing system, made of rustproof treated steel.
- 4 Rustproof treated steel frame, flush mounted, fitted with 2 fixed and 2 swivelling castors Ø 100 mm
- 5 One-piece EPDM seal. Retracting door stop to keep door fixed open.
- 6 Label holder
- **15** 4 flush-mounted handles
- 16 Retracting door stop to keep door fixed open.

